

ISSN 2518-1491 (Online),
ISSN 2224-5286 (Print)

ҚАЗАҚСТАН РЕСПУБЛИКАСЫ
ҰЛТТЫҚ ҒЫЛЫМ АКАДЕМИЯСЫНЫҢ

Х А Б А Р Л А Р Ы

ИЗВЕСТИЯ

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК
РЕСПУБЛИКИ КАЗАХСТАН

N E W S

OF THE ACADEMY OF SCIENCES
OF THE REPUBLIC OF KAZAKHSTAN

**ХИМИЯ ЖӘНЕ ТЕХНОЛОГИЯ
СЕРИЯСЫ**

◆
СЕРИЯ
ХИМИИ И ТЕХНОЛОГИИ
◆
SERIES
CHEMISTRY AND TECHNOLOGY

5 (419)

ҚЫРКҮЙЕК – ҚАЗАН 2016 ж.
СЕНТЯБРЬ – ОКТЯБРЬ 2016 г.
SEPTEMBER – OCTOBER 2016

1947 ЖЫЛДЫҢ ҚАҢТАР АЙЫНАН ШЫҒА БАСТАҒАН
ИЗДАЕТСЯ С ЯНВАРЯ 1947 ГОДА
PUBLISHED SINCE JANUARY 1947

ЖЫЛЫНА 6 РЕТ ШЫҒАДЫ
ВЫХОДИТ 6 РАЗ В ГОД
PUBLISHED 6 TIMES A YEAR

АЛМАТЫ, ҚР ҰФА
АЛМАТЫ, НАН РК
ALMATY, NAS RK

Бас редакторы
х.ғ.д., проф., КР ҮФА академигі **М.Ж. Жұрынов**

Редакция алқасы:

Ағабеков В.Е. проф., академик (Белорус)
Волков С.В. проф., академик (Украина)
Воротынцев М.А. проф., академик (Ресей)
Газалиев А.М. проф., академик (Қазақстан)
Ергожин Е.Е. проф., академик (Қазақстан)
Жармағамбетова А.К. проф. (Қазақстан), бас ред. орынбасары
Жоробекова Ш.Ж. проф., академик (Қырғыстан)
Итқұлова Ш.С. проф. (Қазақстан)
Манташян А.А. проф., академик (Армения)
Пралиев К.Д. проф., академик (Қазақстан)
Баешов А.Б. проф., корр.-мүшесі (Қазақстан)
Бұркітбаев М.М. проф., корр.-мүшесі (Қазақстан)
Джусипбеков У.Ж. проф. корр.-мүшесі (Қазақстан)
Молдахметов М.З. проф., корр.-мүшесі (Қазақстан)
Мансуров З.А. проф. (Қазақстан)
Наурызбаев М.К. проф. (Қазақстан)
Рудик В. проф., академик (Молдова)
Стрельцов Е. проф. (Белорус)
Тәшімов Л.Т. проф., корр.-мүшесі (Қазақстан)
Тодераш И. проф., академик (Молдова)
Халиков Д.Х. проф., академик (Тәжікстан)
Фарзалиев В. проф., академик (Әзіrbайжан)

«КР ҮФА Хабарлары. Химия және технология сериясы».

ISSN 2518-1491 (Online)

ISSN 2224-5286 (Print)

Меншіктенуші: «Қазақстан Республикасының Үлттық ғылым академиясы» Республикалық қоғамдық бірлестігі (Алматы қ.)

Қазақстан республикасының Мәдениет пен ақпарат министрлігінің Ақпарат және мұрагат комитетінде 30.04.2010 ж. берілген №1089-Ж мерзімдік басылым тіркеуіне қойылу туралы куәлік

Мерзімділігі: жылына 6 рет.

Тиражы: 300 дана.

Редакцияның мекенжайы: 050010, Алматы қ., Шевченко көш., 28, 219 бөл., 220, тел.: 272-13-19, 272-13-18,
www.nauka-nanrk.kz / chemistry-technology.kz

© Қазақстан Республикасының Үлттық ғылым академиясы, 2016

Типографияның мекенжайы: «Аруна» ЖК, Алматы қ., Муратбаева көш., 75.

Г л а в н ы й р е д а к т о р
д.х.н., проф.,академик НАН РК **М. Ж. Журинов**

Р е д а к ц и о н а я к о л л е г и я:

Агабеков В.Е. проф., академик (Беларусь)
Волков С.В. проф., академик (Украина)
Воротынцев М.А. проф., академик (Россия)
Газалиев А.М. проф., академик (Казахстан)
Ергожин Е.Е. проф., академик (Казахстан)
Жармагамбетова А.К. проф. (Казахстан), зам. гл. ред.
Жоробекова Ш.Ж. проф., академик (Кыргызстан)
Иткулова Ш.С. проф. (Казахстан)
Манташян А.А. проф., академик (Армения)
Пралиев К.Д. проф., академик (Казахстан)
Баешов А.Б. проф., чл.-корр. (Казахстан)
Буркитбаев М.М. проф., чл.-корр. (Казахстан)
Джусипбеков У.Ж. проф. чл.-корр. (Казахстан)
Мулдахметов М.З. проф., чл.-корр. (Казахстан)
Мансуров З.А. проф. (Казахстан)
Наурызбаев М.К. проф. (Казахстан)
Рудик В. проф.,академик (Молдова)
Стрельцов Е. проф. (Беларусь)
Ташимов Л.Т. проф., чл.-корр. (Казахстан)
Тодераш И. проф., академик (Молдова)
Халиков Д.Х. проф., академик (Таджикистан)
Фарзалиев В. проф., академик (Азербайджан)

«Известия НАН РК. Серия химии и технологии».

ISSN 2518-1491 (Online),

ISSN 2224-5286 (Print)

Собственник: Республиканское общественное объединение «Национальная академия наук Республики Казахстан» (г. Алматы)

Свидетельство о постановке на учет периодического печатного издания в Комитете информации и архивов Министерства культуры и информации Республики Казахстан №10893-Ж, выданное 30.04.2010 г.

Периодичность: 6 раз в год

Тираж: 300 экземпляров

Адрес редакции: 050010, г. Алматы, ул. Шевченко, 28, ком. 219, 220, тел. 272-13-19, 272-13-18,
<http://nauka-nanrk.kz> / chemistry-technology.kz

© Национальная академия наук Республики Казахстан, 2016

Адрес редакции: 050100, г. Алматы, ул. Кунаева, 142,

Институт органического катализа и электрохимии им. Д. В. Сокольского,
каб. 310, тел. 291-62-80, факс 291-57-22, e-mail:orgcat@nursat.kz

Адрес типографии: ИП «Аруна», г. Алматы, ул. Муратбаева, 75

Editor in chief
doctor of chemistry, professor, academician of NAS RK **M.Zh. Zhurinov**

Editorial board:

Agabekov V.Ye. prof., academician (Belarus)
Volkov S.V. prof., academician (Ukraine)
Vorotyntsev M.A. prof., academician (Russia)
Gazaliyev A.M. prof., academician (Kazakhstan)
Yergozhin Ye.Ye. prof., academician (Kazakhstan)
Zharmagambetova A.K. prof. (Kazakhstan), deputy editor in chief
Zhorobekova Sh.Zh. prof., academician (Kyrgyzstan)
Itkulova Sh.S. prof. (Kazakhstan)
Mantashyan A.A. prof., academician (Armenia)
Praliyev K.D. prof., academician (Kazakhstan)
Bayeshov A.B. prof., corr. member (Kazakhstan)
Burkitbayev M.M. prof., corr. member (Kazakhstan)
Dzhusipbekov U.Zh. prof., corr. member (Kazakhstan)
Muldakhmetov M.Z. prof., corr. member (Kazakhstan)
Mansurov Z.A. prof. (Kazakhstan)
Nauryzbayev M.K. prof. (Kazakhstan)
Rudik V. prof., academician (Moldova)
Streltsov Ye. prof. (Belarus)
Tashimov L.T. prof., corr. member (Kazakhstan)
Toderash I. prof., academician (Moldova)
Khalikov D.Kh. prof., academician (Tadzhikistan)
Farzaliyev V. prof., academician (Azerbaijan)

News of the National Academy of Sciences of the Republic of Kazakhstan. Series of chemistry and technology.
ISSN 2518-1491 (Online),
ISSN 2224-5286 (Print)

Owner: RPA "National Academy of Sciences of the Republic of Kazakhstan" (Almaty)
The certificate of registration of a periodic printed publication in the Committee of Information and Archives of the Ministry of Culture and Information of the Republic of Kazakhstan N 10893-Ж, issued 30.04.2010

Periodicity: 6 times a year

Circulation: 300 copies

Editorial address: 28, Shevchenko str., of. 219, 220, Almaty, 050010, tel. 272-13-19, 272-13-18,
<http://nauka-nanrk.kz> / chemistry-technology.kz

© National Academy of Sciences of the Republic of Kazakhstan, 2016

Editorial address: Institute of Organic Catalysis and Electrochemistry named after D. V. Sokolsky
142, Kunayev str., of. 310, Almaty, 050100, tel. 291-62-80, fax 291-57-22,
e-mail: orgcat@nursat.kz

Address of printing house: ST "Aruna", 75, Muratbayev str, Almaty

N E W S

OF THE NATIONAL ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN

SERIES CHEMISTRY AND TECHNOLOGY

ISSN 2224-5286

Volume 5, Number 419 (2016), 144 – 151

UDK 541.138

A. Mamyrbekova, A. Mamitova, A. Tukibayeva, P. Parimbek, A. Mamyrbekova

¹M. Auezov South Kazakhstan state university, Shymkent;

²A. Yasawi International kazakh-turkish university, Turkestan, Kazakhstan)

E-mail: aigul_akm@mail.ru

PRODUCTION OF COPPER POWDERS FROM WATER-DIMETHYLSULPHOXIDE ELECTROLYTES

Abstract. Electrodeposition copper powder of cathodic reduction in organic solvent is investigated and the electrolit, representing solution Cu(NO₃)₂·3H₂O in dimethylsulphoxide (DMSO) is offered. Varying concentration of electrolit within the limits of 0,1-0,6 M and cathodic density of a current 200-1200 A/m², at temperatures 288-348 K it is possible to receive qualitative copper powders with a given structure and dispersity. In work the electrolyte on the basis of aprotic polar solvent – dimethylsulphoxide was elaborated and the optimum conditions permitting to obtain electrolytic copper powders with high current efficiency, which differ in microstructure and morphology were determined. The structure electrolytic copper powders received electrolysis of 0,1-0,6 M of solutions Cu(NO₃)₂·3H₂O in DMSO is studied depending on key parameters of a mode electrolysis - cathodic density of a current and temperature by the roentgenographical analysis.

Key words: Electrodeposition, dimethylsulphoxide, copper(II) nitrate crystallohydrate, current density, copper powder, roentgenography.

Introduction. Among developing directions of modern researches fine-dispersed powders have the particular interest. A microstructure of fine-dispersed powders gives them a number of new properties in comparison with usual materials. Recently it is given the great consideration to fine-dispersed copper powders possessing specific properties thanks to which it is possible their application for development of new effective materials of different purpose [1].

The basic application field of copper powder is powder metallurgy, where it is used for development of various products of constructional, antifriction and electrotechnical purposes, and also composite materials. In so doing copper powder is an intermediate product of copper manufacture and should meet the certain requirements. The electrolytic method allows producing chemically pure copper powders, which have unique, stable properties (a dendritic shape, a dense texture of particles). The basic advantage of the given method is a possibility of regulation of a powder's structure and properties by means of variation of electrolytic deposition parametres and an electrolyte composition. It allows to influence a structure, a size, a shape and a chemical composition of powders [2,3].

A problem of metals' isolation without the accompanying (parallel) reaction of hydrogen release, characteristic for electrolysis of water solutions, can be solved if to use the solvents possessing higher electrochemical stability, than water. Aprotic organic solvents, which do not contain mobile hydrogen and can be reduced at sufficiently high cathodic potentials, are the most admissible in this respect [4-6]. In this connection, in the given work as a solvent it has been chosen dimethyl- sulfoxide (CH₃)₂SO – a cationotropic compound describable by a high dissolving and ionising ability ($\epsilon=47$). Also it is known high adsorption activity of the solvent on a border «copper-electrolyte» [7].

In the work influence of various parametres has been investigated: a current density, temperatures and concentrations for the electroreduction of copper(II) ions in DMSO, a composition and purity of the copper powders produced.

Electrodeposition of a copper powder has been carried out on an electrolysis installation [8] with consecutive switching on an electrolytic cell and a copper coulombmeter. The electrolysis has been performed in a glass constant-temperature electrolytic cell in volume of 150 cm³. Electrodeposition of a copper powder was carried out in galvanostatic mode at a temperature-controlled glass cell equipped with a vinyl plastic cap with parallel fixed anodes, without forced stirring. As a cathode using a cylindrical steel rod that is placed in the center of the lid. The soluble anodes used as a plate made of electrolytically pure copper. The advantage of using soluble anodes is that electrolysis for quite a long time can be performed.

As a direct current source has been applied a universal power supply UIP-2 providing high stabilisation of rectified current. Electric circuit current has been measured by a multirange ampere-voltmeter AVO-5MI.

Quality of the electrolytic powders produced has been estimated visually and according to the microphotos made by means of a scanning electronic microscope J.SM-840 at increase in 2000 times.

The X-ray structural analysis of copper electrolytic powders has been performed on a diffractometer DRON-2,0 (monochromatic CuK_α-radiation). The counter speed is 2 deg/min.

Experimental

The researches of volume and transport properties of copper(II) nitrate crystallohydrate solutions in DMSO have shown, that the electroconductivity maximum is observed in the 0,4 M solution of copper(II) nitrate in DMSO at 288 K, which is displaced to 0,6 M at higher temperatures [9,10]. In this connection, for study of a possibility of a copper powder electrodeposition from dimethylsulfoxide the copper salt's concentration interval was in the limits of 0,1-0,6 M. The solutions with the copper salt concentration of 0,5 M and higher have high viscosity, which decreases the metal ions' mobility.

In the electrolyte used for obtaining a copper powder as a result of the components' interaction probably are formed copper(II) ions, nitrate ions, and also solvated $[Cu(DMSO)_4(H_2O)_2]^{2+}$ complexes and inclusion complex ions – $[(CH_3)_2SONO_3]$ [11], causing electroconductivity of the solution. The influence of DMSO on the copper powder electrocrystallization is obviously connected with its surface-active and complexing properties.

At the current density of 200-300 A/m² it is observed the copper powder de- position, but with lower current efficiency (63-64%). With increase of the current density to 500 A/m² the powder becomes fine-crystalline. The current efficiency of copper powder makes 75-86%. The further growth of current density to 1200 A/m² leads to small decrease in the current efficiency to 81%. The results of copper powder electrodeposition from 0,1 M of $Cu(NO_3)_2 \cdot 3H_2O$ solution in DMSO at T = 288 K are represented in table 1.

Table 1 – Results of the copper powder electrodeposition from 0,1 M $Cu(NO_3)_2 \cdot 3H_2O$ solution in DMSO at T = 288K

№	i_k , A/m ²	CE, %	The powder exterior view and quality
1	200	63,8	dark brown, large dendrites
2	300	64,2	dark brown, coarse-grained
3	400	75,1	dark brown with tints of red, coarse-grained
4	500	86,3	dark red, grained
5	600	86,8	pink, fine-dispersed
6	700	87,9	pink, fine-dispersed
7	800	88,5	pink, fine-dispersed
8	900	88,9	pink, fine-dispersed
9	1000	89,5	pink, fine-dispersed fraction
10	1100	86,2	pink, fine-dispersed fraction
11	1200	81,1	dark pink, fine-dispersed

At the electrolysis with the minimum current density of 100 A/m^2 and temperature of 298 K the dark brown powders with large dendrites are isolated. In the microphoto zoomed in 2000 times it is well visible the crystallites in the size from 45 to 90 microns ingrown into a grained surface. The yield of copper powder on the current is equal 79,1 % (tab.2, fig.1, a).

Table 2 – Results of the copper powder electrodeposition from 0,1 M $\text{Cu}(\text{NO}_3)_2 \cdot 3\text{H}_2\text{O}$ solution in DMSO at $T = 298 \text{ K}$

No	$i_k, \text{A/m}^2$	CE, %	The powder's exterior view and surface morphology (x2000)
1	100	79,1	dark brown, the crystallites in the size of 45-90 micron on the grained surface
2	250	84,2	dark brown, the lengthened crystallites from 30 to 100 micron
3	500	96,8	brown with tints of red, decrease of the grains' average size
4	600	97,3	pink-red, the dendrite-form grains
5	750	97,9	pink, the grains are smaller than at $i_k = 500 \text{ A/m}^2$
6	800	98,2	dark pink, fine-dispersed
7	900	97,5	dark pink, fine-dispersed
8	1000	97,1	dark pink, fine-dispersed

At the current density increase to 250 A/m^2 the dark brown sediments are formed. The electron microscope research has shown that the surface consists from lengthened crystalline grains in the size from 30 to 100 microns. The current yield has increased to 84,2%. The copper powder morphology is represented on fig.1, b.

The further increase in current density to $500-750 \text{ A/m}^2$ leads to the formation of average size grains (fig.1, c).

The copper powders obtained are thickness-uniform, have the dendrite morphology and very high purity. The copper grains have a dendrite form. The current yield of the copper powder practically does not vary and is within 96,8-98%.

With the current density increase above 800 A/m^2 the current yield slowly falls; in this case the light pink fine-dispersed copper powders are precipitated (fig.1, d).

The increase of current density to 1000 A/m^2 leads to the isolation of fine-dispersed powders and causes side processes leading to the formation of by-products, which lower the copper powders' quality and current yield. The electron microscope research has shown that the powder surface represents a uniform layer of small dendrites not exceeding 35 microns (fig.1, e).

The minor temperature increase (to 298 K) of 0,1 M copper nitrate trihydrate- DMSO electrolyte influences the electrolysis indicators: the metal yield considerably increases; the limit of cathodic current density, which provides obtaining a high-quality copper powder rises. Hence, the temperatures increase from $T = 288 \text{ K}$ to 298 K is favourable to isolation of high-quality copper powders from diluted copper nitrate - DMSO solutions. In these conditions at the current density above 1000 A/m^2 there is the reduction of copper powders' quality and current yield.

A roentgenogram of the copper powder produced from a 0,1 M $\text{Cu}(\text{NO}_3)_2 \cdot 3\text{H}_2\text{O}$ - DMSO solution at current density of 100 A/m^2 and temperature of 298 K has the strongly pronounced peaks with reflections distinctive for pure copper: 1,277; 1,81 and $2,08 \text{ \AA}^\circ$, the reflection of $1,81 \text{ \AA}^\circ$ is the most intensive one. The observable peaks testify to high purity and a crystal structure of the copper powder. With the increase of current density to 500 and 750 A/m^2 the roentgenograms are similar the previous one, but it is noticeably observed the increase in intensity of reflections of $1,277 \text{ \AA}^\circ$ and $2,08 \text{ \AA}^\circ$.

The results of X-ray phase analysis of the copper powders produced at constant current density of 800 A/m^2 and different temperatures have shown, that at temperature of 298 K an absolutely pure powder is precipitated. On the X-ray pattern (fig.2) can observe the peaks, characteristic for pure copper ($1,277 \text{ \AA}^\circ$; $1,81 \text{ \AA}^\circ$ and $2,08 \text{ \AA}^\circ$).




Figure 1 – Morphology of the copper powders produced from a 0,1 M solution of copper nitrate trihydrate in DMSO at temperature of 298 K and different current density: a – 100 A/m²; b – 250 A/m²; c – 600 A/m²; d – 800 A/m²; e – 1000 A/m² (zoom 2000)




Figure 2 – An X-ray pattern of the powder produced from a 0,1 M Cu(NO₃)₂·3H₂O-DMSO solution at $i_k = 800 \text{ A/m}^2$ and $T = 298 \text{ K}$

Temperature effect on the copper electrodeposition from 0,1 M copper nitrate trihydrate - DMSO solution has been studied at current density of 800 A/m². The results are represented in table 3.


Table 3 – Results of the copper powder electrodeposition from a 0,1 M Cu(NO₃)₂·3H₂O-DMSO electrolyte at i_k = 800 A/m² and different temperatures

№	T, K	CE, %	The powder exterior view and quality
1	288	88,5	pink, fine-dispersed
2	298	98,2	light pink, fine-dispersed, dense
3	308	94,5	light pink, separate strongly distorted crystal particles on medium-grained background
4	318	86,3	dark pink, grained, dispersed powder
5	328	84,0	dark pink, a surface of the powder is friable; small spheroidal crystallized
6	338	57,1	brick-red, coarse-dispersed
7	348	43,1	dark, coarse-dispersed

From the findings follows, that at the electrolysis of a diluted copper nitrate-DMSO solution the formation of high-quality powders is favoured by low temperatures to 298 K. In these conditions the basic cathode process happens on the equations (1) and (2).



With the rise of temperature to 308 K and above in the electrolyte occurs the breakage of hydrogen bonds that complicates the physicochemical processes and intensifies fluctuations in the solution. As a result of the breakage of nitrate ions-DMSO complexes the overstrain decreases and their reduction in accordance with the equation (3) is facilitated.



As a consequence, the nitrate ion reduction speed considerably increases pH of the cathode zone increases, the metal yield decreases and the powder quality sharply worsens. In the conditions of high basicity in the cathode area a probability of formation of copper(I) slightly soluble compounds, probably CuOH and Cu₂O, increases; these compounds, by-turn, are captured by the growing deposit and causes colouring the powder.

At the rise of temperature to 308 K the roentgenogram along with the pure copper reflections – 1,089 Å°; 1,277 Å°; 1,81 Å°; 2,08 Å°, contains reflections of other phase – 1,51 Å°; 2,12 Å° and 2,45 Å°, which correspond to monovalent copper oxide Cu₂O; obviously, it forms owing to the interaction of copper(I) ions with hydroxyl ions and is joined to the cathode powder. Intensity of these peaks is insignificant.

At temperature of 318 K there are new peaks (1,283 Å°; 3,00 Å°) on the X-ray pattern (fig.3), which also are part of copper(I) oxide. The appearance of new peaks is obviously caused by the increase of copper(I) oxide amount in the copper powder. At the further increase in temperature (to 328 K) new peaks characteristic for copper(I) oxide are not observed, but intensity of the available peaks become stronger. Simultaneously intensity of the copper peaks 1,089 Å° and 1,277 Å° decreases (fig.4).

Inclusions of copper oxide Cu₂O formed on the cathode surface indicate the stepwise reduction of Cu²⁺ ions on the cathode.




Figure 3 – An X-ray pattern of the powder produced from a 0,1 M Cu(NO₃)₂·3H₂O-DMSO solution at $i_k = 800 \text{ A/m}^2$ and $T = 318 \text{ K}$




Figure 4 – An X-ray pattern of the powder produced from a 0,1 M Cu(NO₃)₂·3H₂O-DMSO solution at $i_k = 800 \text{ A/m}^2$ and $T = 328 \text{ K}$

The influence of various factors (concentration, temperature, current density) on the copper electrocrystallization from a dimethylsulfoxide electrolyte can be explained as follows.

The main cathode process is the reduction of copper ions expressed by the equations (1-2). Discharge of Cu^{2+} complex ions is connected with penetration through a dense adsorption film consisting of DMSO molecules.

It leads to the certain inhibition of complex copper(II) ion electroreduction. In these conditions, according to the theory, on the cathode it is isolated a more fine-dispersed copper powder, than at the electrolysis of water solutions of simple salts, which do not contain surface-active additives.

The rise of temperature (above 298 K) reduces adsorption activity of DMSO molecules, sharply increases reactionary activity of nitrate ions solvated by the molecules of an organic solvent in a less degree.

Presence of small water amounts in the solution (to 3,6 %), temperature growth and high polarization of the cathode most likely accelerate the reduction speed of more reactive nitrate ions; it leads to inclusion of copper(I) insoluble compounds in the cathodic powder, and, it is quite probable, the modification of growing metal crystals occurs at the expense of these compounds and not the solvent molecules.

The experiment results have shown that high-quality copper powders can be obtained from copper nitrate-dimethylsulfoxide solutions by means of electrolysis both diluted and concentrated solutions. From the diluted (0,1 M) solutions high-quality copper powders can be produced to 1000 A/m^2 . Use of higher concentrations allows to produce qualitative coverings in wider interval of current density (in a 0,4 M solution – to 2200 A/m^2).

The rise of temperature (above 303 K) and current density (above 1000 A/m^2) causes the side reactions leading to formation of by-products; as a result of it the copper powder quality and yield decrease. The ion association, increasing with temperature growth, and increase of the electrolyte viscosity in concentrated copper nitrate trihydrate-DMSO solutions, reducing conductivity of the solution, cause difficulties of the copper ion reduction and quality loss of the copper powders produced.

The temperature effect on electrolysis in the investigated concentration interval has shown, that the rise of temperature to 303 K and above accelerates the reaction (2) reducing the copper current yield. In these conditions the accumulation of OH^- ions in the cathode zone, which is characterized by high basicity, leads to the formation of copper(I) oxide, which contaminates the cathodic deposit. The electrolytic deposits obtained are non-uniform by thickness, have an ordinary appearance. The presence of copper(I) oxide in the cathodic deposits is confirmed by the X-ray phase analysis data.

The temperature growth above 303 K also promotes the breakage of hydrogen bonds and disintegration of heteromolecular complexes on molecules of DMSO and H_2O . Also this phenomenon is probably accompanied by the dissociation of solvated complexes of copper(II) ions and inclusion complex ions, that creates the favorable conditions for electrolyte ion association; this phenomenon was confirmed by the results of transport properties of the solutions.

It is necessary to note the electrolytes, which contain 0,6 M of copper(II) nitrate crystalline hydrate. The copper yield from these solutions is lower than one from the diluted solutions. The copper powder obtained from such solutions has an unsatisfactory appearance in all interval of the investigated temperatures and current density. A dominant cause of it is the copper(I) sulphide formation and its inclusion in the powder. This supposition is confirmed by chemical and X-ray phase analyses.

Conclusion. Thus, the optimum conditions for obtaining high-quality fine-dispersed copper powders are concentration of 0,1-0,4 M $\text{Cu}(\text{NO}_3)_2 \cdot 3\text{H}_2\text{O}$ and temperature of 283-298 K. The ion association, increasing with the temperature growth, and the increase of electrolyte viscosity in concentrated copper nitrate trihydrate-dimethyl sulfoxide solutions, reducing conductivity of the solution, cause the difficulties of copper ion reduction and deterioration of the powders produced.

REFERENCES

- [1] Sosnovskij G.N., Sosnovskaja N.G. The electrolytic production of metal powders and the electrolysis of molten media. Angarsk: AGTA, **2006**. 91 p. (in Russ.).
- [2] Nichiporenko O.S., Pomosov A.V., Nabojchenko S.S. The powders and copper alloys. M.: Metallurgija, **1988**. 204 p. (in Russ.).
- [3] Nomberg M.I. Production of electrolytic copper powder method. M.: Metallurgija, **1971**. 134 p. (in Russ.).

- [4] Savenko P.V., Trachuk S.V. Jelektroosazhdzenie medi iz nevodnyh rastvorov. Kiev, **1988**. 17 p. Dep. v Ukr NIINTI 858 Uk 88. (in Russ.).
- [5] Gusel'nikova O.V., Obrazcov S.V. Jelektroosazhdzenie metallov i splavov iz nevodnyh jeklitolitov. Cherkassy, **1989**. 58 p. Dep. v ONIITJehim. N826 XII 89. (in Russ.).
- [6] Vahidov R.S. // Jelektrohimija, **1994**, T.30, №97, 1165-1166 (in Russ.).
- [7] Vahidov R.S., Mamyrbekova A.K., Dzhemilev U.M., Selimov F.A., Starchenko A.A. // Tez. dokl. X Vseross. soveshh. «Sovershenstvovanie tehnologii gal'venopokrytij». Kirov: Izd. VjatGTU, **1997**, 112 (in Russ.).
- [8] Kudrjavceva V.N., Varupaev V.N. Practical works on applied electrochemistry. L.: Himija, **1990**. 304 p. (in Russ.).
- [9] Mamyrbekova A.K. //Russ. J. Phys. Chem., **2013**, V. 87, N.3, 414-417 (in Eng.).
- [10] Mamyrbekova A.K. //Russ. J. Gen. Chem., **2013**, V. 83, N. 10, 1799–1802 (in Eng.).
- [11] Matrin D., Hauthal H. Dimethylsulfoxid. Berlin: AcademieVerlag, **1971**. 494 p. (in Eng.).

А. Мамырбекова¹, А. Мамитова¹, А. Тукибаева¹, П. Паримбек¹, А. Мамырбекова²

М. Эуезов атындағы Оңтүстік Қазақстан мемлекеттік университеті, Шымкент;
* Қ.А. Ясауи атындағы Халықаралық қазақ-түрк университеті, Түркістан, Қазақстан

СҰЛЫ-ДИМЕТИЛСУЛЬФОКСИДТІ ЭЛЕКТРОЛИТ ЕРІТІНДІЛЕРДЕН МЫС ҰНТАҚТАРЫН АЛУ

Аннотация. Жұмыста органикалық еріткіште мыс ұнтағын катодты тотықсыздану арқылы электротұндыруы зерттеліп, құрамында $\text{Cu}(\text{NO}_3)_2 \cdot 3\text{H}_2\text{O}$ және диметилсульфоксиді (ДМСО) бар ерітінді электролит ретінде ұсынылған. Электролиттің концентрациясын 0,1-0,6 M, катодты тоқ тығыздығын 200-1200 A/m² және температураны 288-348 K аралығында өзгере отырып, белгілі құрылымы мен дисперстілікке ие сапалы мыс ұнтақтарын алуға болады. Жұмыста аprotонды полярлы еріткіш – диметилсульфоксид негізінде мыстың тұндыруына арналған электролит ұсынылған. Микрокұрылымы мен морфологиясы бойынша ерекшеленетін, тоқ бойынша жоғары шығымымен түзілетін мыстың электролиттік ұнтағын аладың оптимальды жағдайлары анықталған. Электролиздің негізгі параметрлеріне – катодты тоқ тығыздығы мен температураға байланысты 0,1-0,6 M $\text{Cu}(\text{NO}_3)_2 \cdot 3\text{H}_2\text{O}$ – ДМСО ерітінділерден алынған мыстың электролиттік ұнтақтарының құрылымы рентгенографиялық талдаумен зерттелген.

Түйін сөздер: электротұндыру, диметилсульфоксид, мыс(II) нитратының кристаллогидраты, тоқ тығыздығы, мыс ұнтағы, рентгенография.

А. Мамырбекова¹, А. Мамитова¹, А. Тукибаева¹, П. Паримбек¹, А. Мамырбекова²

¹Южно-Казахстанский государственный университет им. М. Ауэзова, Шымкент;
²Международный казахско-турецкий университет им. Х.А. Ясави, Туркестан, Казахстан)

ПОЛУЧЕНИЕ МЕДНЫХ ПОРОШКОВ ИЗ ВОДНО-ДИМЕТИЛСУЛЬФОКСИДНЫХ РАСТВОРОВ ЭЛЕКТРОЛИТОВ

Аннотация. Исследовано электроосаждение медного порошка путем катодного восстановления в органическом растворителе и предложен электролит, представляющий раствор $\text{Cu}(\text{NO}_3)_2 \cdot 3\text{H}_2\text{O}$ в диметилсульфоксиде (ДМСО). Варьируя концентрацию электролита в пределах 0,1-0,6 M и катодную плотность тока 200-1200 A/m², при температурах 288-348 K можно получить качественные медные порошки с заданной структурой и дисперсностью. В работе предложен электролит на основе аprotонного полярного растворителя – диметилсульфоксида и определены оптимальные условия, позволяющие получать электролитические порошки меди с высоким выходом по току, различающиеся микроструктурой и морфологией. Структура электролитических порошков меди, полученных электролизом 0,1-0,6 M растворов $\text{Cu}(\text{NO}_3)_2 \cdot 3\text{H}_2\text{O}$ в ДМСО изучена в зависимости от основных параметров режима электролиза – катодной плотности тока и температуры рентгенографическим анализом.

Ключевые слова: электроосаждение, диметилсульфоксид, кристаллогидрат нитрата меди(II), плотность тока, медный порошок, рентгенография.

МАЗМУНЫ

<i>Нурмаканов Е.Е., McCue A.J., Anderson J.A., Иткулова Ш.С., Кусанова Ш.К.</i> Со-құрамды отырызылған катализаторларда CO ₂ немесе CO ₂ -H ₂ O қөмегімен метанның конверсиясы	5
<i>Дергачева М.Б., Хусурова Г.М., Пузикова Д.С., Немкаева Р.Р., Яскевич В.И., Митъя К.А.</i> CdSe жұқа қабықтарын электротұндыруына ПАВ-тың әсері.....	12
<i>Мансуров З.А., Тулепов М.И., Казаков Ю.В., Габдрашова Ш.Е., Байсейтов Да.А., Турсынбек С., Дальтон Алан Б.</i> Түрлендірілген компоненттер негізіндегі пиротехникалық баяулатқыш құрам.....	21
<i>Бишиимбаева Г.К., Жұмабаева Д.С.</i> Өнеркәсіп полимерлерін тікелей құқірттендіру арқылы катод материалдарының жаңа компоненттерін алудың технологиялық тиімді әдістері.....	28
<i>Жармагамбетова А.К., Ауезханова А.С., Джумекеева А.И., Тұмабаев Н.Ж.</i> ПВПД-мен түрлендірілген биметалды катализатордың н-октанды жұмсақ жағдайда тотықтырудагы каталитикалық қасиеттері.....	39
<i>Туктін Б. Т., Жандаров Е.К., Шаповалова Л.Б., Тенизбаева А.С.</i> Модифицирленген цеолитқұрамды адюмоқсидті катализаторларында мұнай фракцияларын гидроөндөу.....	46
<i>Налибаева А.М., Сасыкова Л.Р., Котова Г.Н., Богданова И.О.</i> Азот оксидін көмірсутектермен тотықсыздандыруға арналған уларға төзімді және құрамында цеолит бар метал блоктарындағы катализаторлардың синтезі мен сынақтамасы.....	55
<i>Дергачева М.Б., Хусурова Г.М., Уразов К.А.</i> Кварциты микробаланс пен вольтамперометрия әдістерімен құқірт қышқыл және сульфосалицил қышқыл негізіндегі электролиттерден мыстың электротұндыруының зерттелуі.....	65
<i>Сагынтаева Ж.И., Қасенова Ш.Б., Исабаева М.А., Қасенов Б.Қ., Куанышбеков Е.Е.</i> NdNaFeCrMnO _{6,5} ферро-хромо-манганиттің жылу сыйымдылығы мен термодинамикалық функциялары.....	74
<i>Ахметқарімова Ж.С., Молдахметов З.М., Ордабаева А.Т., Байкенов М.И., Богжанова Ж.К., Ескендиров Т.Р.</i> Антрацен және бензотиофен полиараматикалық коспасының тепе-тәндік кинетикалық анализі.....	79
<i>Алімжанова М.Б.</i> ҚФМЭ-ГХ-МС әдісімен Алматы сутұндырығысы сұында үшқыш органикалық ластаушылардың скринингі.....	85
<i>Баешов А.Б., Егербаева С.С., Кадирбаева А.С., Баешова А.Қ.</i> Анонты импульстік токпен поляризацияланған никельдің фосфор қышқылы ерітіндісіндегі электрохимиялық қасиеті.....	93
<i>Бектенов Н.А., Самойлов Н.А., Садыков К.А., Байдуллаева А.К., Абдрабиева Г. Е.</i> Мазут және эпоксиакрилаттар негізінде алынған жаңа фосфорқұрамдас иониттер қөмегімен Cu (II) және Fe (II) иондарын сорбциялау.....	99
<i>Закарина Н.А., Ақурпекова А.К., Далелханұлы О.</i> Бағаналы алноминий монтмориллонитіне отырызылған Pt-катализаторының K-гексан изомеризациясындағы тұрақтылығы.....	104
<i>Рахметова¹ К.С., Сасыкова Л.Р., Гильмундинов Ш.А., Нурахметова М.С., Бердібекова М.А., Калықбердиев М.К., Масенова А.Т., Башева Ж.Т.</i> Автокөлік және мұнай жылыту пештерінің улағыш шығарылударын бейтараптандыруға арналған блок металдық тасымалдаушылардың жасалған катализаторлар.....	111
<i>Сасыкова Л.Р., Налибаева А., Гильмундинов Ш.А.</i> Шынайы жағдайлардағы эксплуатация кезінде пайданылған газдарды тазартуға арналған металдық блоктардағы катализаторлардың синтездеу және сынау.....	118
<i>Сасыкова Л.Р., Калықбердиев М.К., Башева Ж.Т., Масенова А.Т.</i> Бензин фракцияларын жоғары қысымда сұйық күйде гидрлеу.....	126
<i>Сасыкова Л.Р., Нурахметова М.С., Гильмундинов Ш.А., Жумаканова А.С., Рахметова К.С., Калықбердиев М.К., Башева Ж.Т., Масенова А.Т.</i> Присадкалар мен экологиялық таза жана ресурслардың катализатік синтезі.....	135
<i>Мамырбекова А., Мамитова А., Тукибаева А., Паримбек П., Мамырбекова А.</i> Сұлы-диметилсульфоксидті электролит ерітінділерден мыс ұнтақтарын алу.....	144
<i>Мамырбекова А., Мамитова А., Тукибаева А., Паримбек П., Мамырбекова А.</i> Электролиттегі металл иондарының күйіне байланысты оның электротұндыру кезіндегі тазалығы.....	152
<i>Тұнгатарова С.А., Байжуманова Т.С., Жексенбаева З.Т., Абдухалыков Да.Б., Жумабек М., Касымхан К., Сарсенова Р.</i> Жеңіл алкандардың сутек пен сутекті коспага тотығуы.....	157
<i>Бектұрғанова Н.Е., Керімжұлова М.Ж., Тлеуова А.Б., Шарипова А.А., Айдарова С.Б.</i> Алматы қаласы Әуезов ауданының ағын (коммуналды) сұын табиги отандық адсорбенттермен тазалау.....	168
<i>Сасыкова Л.Р., Налибаева А.М., Богданова И.О.</i> Азот оксидін көмірсутектердің қөмегімен тотықсыздандыруға арналған метал блокты тасымалдаушылар негізіндегі цеолит-құрамдас каталитикалық жүйелер.....	177
<i>Сасыкова Л.Р., Налибаева А.</i> Қөмірсутектерді тотықтыруға және азот оксидін тотықсыздандыруға арналған метал блоктың тасымалдаушылардың каталитикалық жүйелердің зерттемелері.....	186
<i>Стажок В.Н., Султанбек У., Фогель Л.А.</i> Сульфат ерітінділеріндегі фосфатталған темірге гидроксиламиннің әсері	194
<i>Сейлханова Г.А., Курбатов А.П., Березовский А.В., Усипбекова Е.Ж., Наурызбаев М.К.</i> Таллий(III) оксидінің электротехникалық тұнудың еру ерекшеліктері	200
<i>Қасенова Ш.Б., Мұқышева Г.К., Байсаров Г.М., Қасенов Б.Қ., Сагынтаева Ж.И., Әдекенов С.М., Хасенова Р.Ж.</i> Флавоноид туындылары цирсилинеол, артемизетиннің термодинамикалық қасиеттері.....	206
<i>Кусанова Ш.К., Кустов Л.В., Иткулова Ш.С., Тұмабаева А.И., Бөлеубаев Е.А., Шаповалов А.А.</i> Құрамында Со бар биметалды катализаторлардағы CO ₂ –нің гидрленуі	211

СОДЕРЖАНИЕ

<i>Нурмаканов Е.Е., McCue A.J., Anderson J.A., Иткулова Ш.С., Кусанова Ш.К.</i> Конверсия метана диоксидом углерода или CO ₂ -H ₂ O на Со-содержащих нанесенных катализаторах.....	5
<i>Дергачева М.Б., Хусурова Г.М., Пузикова Д.С., Немкаева Р.Р., Яскевич В.И., Митъ К.А.</i> Влияние ПАВ на электроосаждение тонких пленок CdSe.....	12
<i>Мансуров З.А., Тулепов М.И., Казаков Ю.В., Габдрашова Ш.Е., Байсейтов Д.А., Турсынбек С., Дальтон Алан Б.</i> Пиротехнический замедлительный состав на основе модифицированных компонентов.....	21
<i>Бишимбаева Г.К., Жумабаева Д.С.</i> Технологичные методы получения новых компонентов катодных материалов прямым осаждением промышленных полимеров.....	28
<i>Жармагамбетова А.К., Ауезханова А.С., Джумекеева А.И., Тумабаев Н.Ж.</i> Каталитические свойства ПВПД-модифицированных биметаллических катализаторов окисления н-октана в мягких условиях.....	39
<i>Туктин Б.Т., Жандаров Е.К., Шаповалова Л.Б., Тенизбаева А.С.</i> Гидропереработка различных нефтяных фракций на модифицированных алюмоксидных катализаторах.....	46
<i>Налибаева А.М., Сасыкова Л.Р., Котова Г.Н., Богданова И.О.</i> Синтез и испытание стабильных к ядам цеолитсодержащих катализаторов на металлических блоках для восстановления оксида азота углеводородами.....	55
<i>Дергачева М.Б., Хусурова Г.М., Уразов К.А.</i> Исследование электроосаждения меди из электролитов на основе серной и сульфосалициловой кислот методами кварцевого микробаланса и вольтамперометрии.....	65
<i>Сагинтаева Ж.И., Касенова Ш.Б., Исабаева М.А., Касенов Б.К., Куанышбеков Е.Е.</i> Теплоемкость и термодинамические функции ферро-хромо-магнанита NdNaFeCrMnO _{6.5}	74
<i>Ахметкаримова Ж.С., Мулдахметов З.М., Ордабаева А.Т., Байкенов М.И., Божсанова Ж.К., Ескендиров Т.Р.</i> Равновесно-кинетический анализ полиароматической смеси антрацена и бензотиофена	79
<i>Алимжанова М.Б.</i> Скрининг летучих органических загрязнителей в воде Алматинского водоотстойника методом ТФМЭ-ГХ-МС.....	85
<i>Баешов А.Б., Егеубаева С.С., Кадирбаева А.С., Баешова А.К.</i> Электрохимическое поведение никелевого электрода при поляризации анодным импульсным током в растворе фосфорной кислоты.....	93
<i>Бектенов Н.А., Самойлов Н.А., Садыков К.А., Байдуллаева А.К., Абдрадиева Г.Е.</i> Сорбция ионов Cu (II) и Fe (II) новым фосфор-содержащим ионообменником на основе эпоксиакрилатов и мазута.....	99
<i>Закарина Н.А., Акрупекова А.К., Далелханулы О.</i> Стабильность Pt-катализаторов, нанесенных на алюминиевый столбчатый монтмориллонит, в изомеризации Н-гексана.....	104
<i>Рахметова К.С., Сасыкова Л.Р., Гильмундинов Ш.А., Нурахметова М.С., Бердебекова М.А., Калықбердиев М.К., Масенова А.Т., Башева Ж.Т.</i> Катализаторы на блочных металлических носителях для нейтрализации токсичных выбросов автотранспорта и печей подогрева нефти.....	111
<i>Сасыкова Л.Р., Налибаева А., Гильмундинов Ш.А.</i> Синтез и испытания катализаторов на металлических блоках для очистки выхлопных газов в реальных условиях эксплуатации	118
<i>Сасыкова Л.Р., Калықбердиев М.К., Башева Ж. Т., Масенова А.Т.</i> Жидкофазная гидрогенизация бензиновых фракций при повышенном давлении.....	126
<i>Сасыкова Л.Р., Нурахметова М.С., Гильмундинов Ш.А., Жумаканова А.С., Рахметова К.С., Калықбердиев М.К., Башева Ж.Т., Масенова А.Т.</i> Катализитический синтез присадок и экологически чистого топлива	135
<i>Мамырбекова А., Мамитова А., Тукибаева А., Паримбек П., Мамырбекова А.</i> Получение медных порошков из водно-диметилсульфоксидных растворов электролитов.....	144
<i>Мамырбекова А., Мамитова А., Тукибаева А., Паримбек П., Мамырбекова А.</i> Чистота электроосаждаемого металла в зависимости от состояния его ионов в электролите.....	152
<i>Тунгатарова С.А., Байжуманова Т.С., Жексенбаева З.Т., Абдухалыков Д.Б., Жумабек М., Касымхан К., Сарсенова Р.</i> Окисление легких алканов в водород и водородсодержащую смесь.....	157
<i>Бектурганова Н.Е., Керимкулова М.Ж., Тлеуова А.Б., Шарипова А.А., Айдарова С.Б.</i> Очистка сточных (коммунальных) вод Ауэзовского района г.Алматы отечественными адсорбентами.....	168
<i>Сасыкова Л.Р., Налибаева А.М., Богданова И.О.</i> Цеолитсодержащие каталитические системы на металлических блочных носителях для восстановления оксида азота углеводородами.....	177
<i>Сасыкова Л.Р., Налибаева А.М.</i> Разработка каталитических систем на металлических блочных носителях для окисления углеводородов и восстановления оксида азота.....	186
<i>Стацик В.Н., Султанбек У., Фогель Л.А.</i> Влияние гидроксиламина на фосфатирование железа в сульфатных растворах.....	194
<i>Сейлханова Г.А., Курбатов А.П., Березовский А.В., Усипбекова Е.Ж., Наурызбаев М.К.</i> Особенности электрохимического осаждения и растворения оксида таллия(III).....	200
<i>Касенова Ш.Б., Мукушева Г.К., Байсаров Г.М., Касенов Б.К., Сагинтаева Ж.И., Адекенов С.М., Хасенова Р.Ж.</i> Термодинамические свойства производных флавоноидов цирсилинеола, артемизетина.....	206
<i>Кусанова Ш.К., Кустов Л.М., Иткулова Ш.С., Тумабаева А.И., Болеубаев Е.А., Шаповалов А.А.</i> Гидрирование CO ₂ на биметаллических Co-Mo/Al ₂ O ₃ катализаторах.....	211

CONTENTS

Nurmakanov Y.Y., McCue A.J., Anderson J.A., Itkulova S.S., Kussanova S.K. Methane reforming by CO ₂ or CO ₂ -H ₂ O over Co-containing supported catalysts.....	5
Dergacheva M.B., Khussurova G.M., Puzikova D.S., Nemkaeva R.R., Yaskevich V.I., Mit'K.A. The influence of SAS on CdSe thin films electrodeposition.....	12
Mansurov Z.A., Tulepov M.I., Kazakov Y.V., Gabdrashova Sh.E., Baiseitov D.A., Tursynbek S., Dalton Alan B. Pyrotechnic delay composition based on modified components.....	21
Bishimbayeva G.K., Zhumaabayeva D.S. Technological methods of receiving new components of cathodic materials by direct sulphuration of industrial polymers.....	28
Zharmagambetova A.K., Auyezhanova A.S., Jumekeyeva A.I., Tumabayev N.Zh. The catalytic properties of the bimetallic PVPD-modified catalysts of n-octane oxidation under mild conditions.....	39
Tuktin B.T., Zhandarov E.K., Shapovalova L.B., Tenizbaeva A.S. The hydroprocessing of different oil fractions on modified alumina catalysts.....	46
Nalibayeva A., Sasykova L.R., Kotova G.N., Bogdanova I.O. Synthesis and testing of the stable to poisons zeolite-containing catalysts on the metal blocks for reduction of nitrogen oxide by hydrocarbons.....	55
Dergacheva M.B., Khussurova G.M., Urazov K.A. The investigation of copper electrodeposition from electrolytes on base sulfur and sulfosalicylic acids by quartz microgravimetry and voltammetry methods.....	65
Sagintaeva Zh.I., Kasenova Sh.B., Issabayeva M.A., Kasenov B.K., Kuanyshbekov E.E. Heat capacity and thermodynamic functions ferro-chrome-manganite NdNaFeCrMn _{6.5}	74
Akhmetkarimova Zh.S., Muldakhmetov Z.M., Ordabaeva A.T., Baikenov M.I., Bogzhanova Zh.K., Eskendiyev T.R. Equilibrium kinetic analysis of poly aromatic mixture anthracene and benzo thiophene.....	79
Alimzhanova M.B. Screening of volatile organic pollutants in water of Almaty Lake-settler by SPME-GC-MS.....	85
Bayeshov A.B., Yegeubayeva S.S., Kadirkayeva A.S., Bayeshova A.K. Electrochemical behavior of the nickel electrode during polarization of the anodic pulse current in the phosphoric acid solution.....	93
Bektenov N.A., Samoilov N.A., Sadykov K.A., Baidullaeva A.K., Abdraliyeva G.E. Sorption Cu (II) and Fe (II) IONS new phosphorus-containing ion exchanger based on fuel oil and epoxyacrylates.....	99
Zakarina N.A., Akurpekova A.K., Dalelkhanuly O. Stability of Pt-catalyst applied on aluminium pillared montmorillonite in N-hexane isomerization.....	104
Rakhmetova K.S., Sasykova L.R., Gil'mundinov Sh.A., Nurakhmetova M.S., Berdibekova M.A., Kalykberdiyev M.K., Massenova A.T., Basheva Zh.T. Catalysts on block metal carriers for neutralization of toxic emissions of motor transport and furnaces of oil heating	111
Sasykova L.R., Nalibayeva A., Gil'mundinov Sh.A. Synthesis and tests of catalysts on metal blocks for cleaning of exhaust gases in real service conditions.....	118
Sasykova L.R., Kalykberdiyev M.K., Basheva Zh.T., Massenova A.T. Liquid phase hydrogenation of gasoline fractions at elevated pressure.....	126
Sasykova L.R., Nurakhmetova M.S., Gil'mundinov Sh.A., Zhumakanova A.S., Rakhmetova K.S., Kalykberdiyev M.K., Basheva Zh.T., Massenova A.T. Catalytic synthesis of additives and ecologically pure fuel.....	135
Mamyrbekova A., Mamitova A., Tukibayeva A., Parimbek P., Mamyrbekova A. Production of copper powders from water-dimethylsulphoxide electrolytes.....	144
Mamyrbekova A., Mamitova A., Tukibayeva A., Parimbek P., Mamyrbekova A. Purity of electrolytic reduction in metal depending on the state of its ions in the electrolyte.....	152
Tungatarova S.A., Baizhumanova T.S., Zheksenbaeva Z.T., Abdughalykov D.B., Zhumabek M., Kassymkan K., Sarsenova R. Oxidation of Light Alkanes into Hydrogen and Hydrogen-containing Mixture.....	157
Bekturganova N., Kerimkulova M., Tleuova A., Sharipova A., Aidarova S. Purification of waste water in Auezov district, Almaty, with the help of the Kazakhstani adsorbents.....	168
Sasykova L.R., Nalibayeva A., Bogdanova I.O. Zeolite-containing catalytic systems on the metal block carriers for reduction of nitrogen oxide by hydrocarbons.....	177
Sasykova L.R., Nalibayeva A. Development of catalytic systems on metal block carriers for oxidation of hydrocarbons and reduction of nitrogen oxide.....	186
Statsjuk V.N., Sultanbek U., Fogel L.A. Effect of hydroxylamine on phosphating iron in sulphate solution.....	194
Seilkhanova G.A., Kurbatov A.P., Berezovski A.V., Ussipbekova E.Zh., Nauryzbayev M.K. Features of the electrochemical deposition and dissolution of thallium oxide (III).....	200
Kasenova S.B., Mukusheva G.K., Baysarov G.M., Kasenov B.K., Sagintaeva J.I., Adekenov S.M., Hasenova R.Zh. Thermodynamic properties derivatives of flavonoids cirsilineol, artemisetine.....	206
Kussanova S.K., Kustov L.M., Itkulova S.S., Tumabayeva A.I., Boileubayev Y.A., Shapovalov A.A. CO ₂ hydrogenation over bimetallic Co-Mo/Al ₂ O ₃ catalysts.....	211

Publication Ethics and Publication Malpractice in the journals of the National Academy of Sciences of the Republic of Kazakhstan

For information on Ethics in publishing and Ethical guidelines for journal publication see <http://www.elsevier.com/publishingethics> and <http://www.elsevier.com/journal-authors/ethics>.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis or as an electronic preprint, see <http://www.elsevier.com/postingpolicy>), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyright-holder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct (http://publicationethics.org/files/u2/New_Code.pdf). To verify originality, your article may be checked by the Cross Check originality detection service <http://www.elsevier.com/editors/plagdetect>.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.

Правила оформления статьи для публикации в журнале смотреть на сайте:

[www:nauka-nanrk.kz](http://www.nauka-nanrk.kz)

<http://www.chemistry-technology.kz/index.php/ru/>

ISSN 2518-1491 (Online), ISSN 2224-5286 (Print)

Редакторы: *M. С. Ахметова, Т. А. Апендиев, Д.С. Аленов*
Верстка на компьютере *A.M. Кульгинбаевой*

Подписано в печать 15.10.2016.
Формат 60x881/8. Бумага офсетная. Печать – ризограф.
13,6 п.л. Тираж 300. Заказ 5.

*Национальная академия наук РК
050010, Алматы, ул. Шевченко, 28, т. 272-13-18, 272-13-19*